



PCB LAYOUT
Layout Tolerance: ±0.20mm

NOTE:

1. Material
.Plunger: Brass
2. Plating
.Contact surface: 1u" minimum Au over 80~100u" Ni
3. Electrical
.Rated Current & Voltage: DC 12V; AC 1~1.65A, 24H
.Contact Resistance: 25mΩ maximum
4. RoHS COMPLIED PRODUCT.
5. Elasticity: Stroke 0mm: 10gf Stroke 0.25mm: 50gf Stroke 1.50mm (or fully compressed): 100~150gf
6. Life (Million): stroke range Max 0.5~4mm
Stroke 10000次
7. Temperature: -40°~150°
8. Use: ELECTRONIC PHOTOGRAPHY: POWER, MOBILE PHONE, ANTENNA, GROUND, BATTERY CONTACT

DIM	TOL	DIM	TOL
X.		X"	3'
X.X	±0.20	X.X"	
X.XX	±0.15	X.XX"	
X.XXX	±0.10	X.XXX"	



深圳市泰科汉泽精密电子有限公司
Tyco Hanconn Precision Electronics

DRAW NO.	DATE	MATERIAL: Brass C3604	DRAW NAME:	
DESIGN: 譚立強	2012.02.13	FINISH: Au1~3u", Ni, 80~120u"	SEE TABLE	
CHECK:		FILE:		
REVIEW:		P/N: SEE TABLE		
		REV. A1	SCALE N/A	UNIT: mm
				SHEET: 1/1