


PCB LAYOUT  
Layout Tolerance: ±0.20mm


变更针头与针管结构



NOTE:

- Material  
.Plunger: Brass
- Plating  
.Contact surface: 3u" minimum Au over 80~100u" Ni
- Electrical  
.Rated Current & Voltage: DC 12V; AC 1~1.65A, 24H  
.Contact Resistance: 25mΩ maximum
- RoHS COMPLIED PRODUCT.
- Elasticity: Stroke 0mm: 10gf Stroke 0.25mm: 50gf Stroke 1.60mm (or fully compressed): 100-150gf
- Life (Million): stroke range Max 0.5~4mm  
Stroke 10000 times
- Temperature: -40°~150°
- Use: Electronic photography: power, mobile phone, antenna, ground, battery contact.

DIM	TOL	DIM	TOL
X.		X'	3'
X.X	±0.20	X.X'	
X.XX	±0.15	X.XX'	
X.XXX	±0.10	X.XXX'	


 深圳市泰科汉泽精密电子有限公司  
**Tyco Hanconn Precision Electronics**  
 Spring Probe

DRAW NO.	DATE	MATERIAL: Brass C3604	DRAW NAME:	
DESIGN: 譚立強	2012.02.13	FINISH: Au3u", Ni, 80~120u"	SEE TABLE	
CHECK:		FILE:		
REVIEW:		P/N: SEE TABLE		
		REV. A1	SCALE N/A	

UNIT: mm	SHEET: 1/1		
----------	------------	---	---